



AlarmPath *Summary Data*

Cellular Alarm Communication Device



The **AP-S Series** provides a summary data wireless communication path from the alarm panel to any central station.

Product Highlights

- **AP-S-LTE** - Operates on the LTE Long Term Evolution cellular networks.
- **AP-S-CDMA** - Operates on nationwide CDMA cellular networks.
- Summary data reporting of up to four unique conditions.
- Ideal for back-up/redundant reporting.
- Discrete inputs triggered in as little as 750 milliseconds.
- SmartChannel™ detects burg and fire from the bell output.
- Reports to any central station. No additional equipment required.
- Daily, weekly, or monthly supervisory test options.
- Powered from the panel. No additional power supply/battery required.
- Optional High-Security Output (HSO) trips if cellular coverage is lost, causing panel alert.
- Designed, manufactured and supported in the USA.

Product Benefits

- **Save Time:** Fast, simple installation with only a few wires to connect. All units are factory programmed.
- **Save Money:** Straightforward billing with no activation fees, complicated programs or unrealistic minimums. Low upfront equipment pricing reduces your initial cash outlay.
- **Increase RMR:** Wireless reporting increases RMR while saving your customer money by eliminating land lines.
- **Increase Profit:** CRN Wireless devices offer a simple, cost-effective means to grow your sales and increase your profit.

Technical Specifications

- Radio Transceiver: UMTS quad band.
 - AP-S-LTE CAT1 penta band.
 - AP-S-CDMA 1xRTT dual band.
- Power Source: 12VDC from the alarm panel.
- Standby power consumption: < 20 mA.
- Transmit power consumption: < 2 A for less than one second.
- Dimensions: 7.75"H x 3.25"W x 1.5"D (dimensions exclude antenna).

CRN Wireless
99 Mark Tree Road, Centereach, NY 11720
1-866-252-7672

www.crnwireless.com